



Managing Search Results
Filter and drill down results to find important information

LEARN MORE

Dashboard / Search / CENTRIFUGAL FIRE PUMPS, VERTICAL TURBINE | UL Product IQ

QXXW.EX28018 - CENTRIFUGAL FIRE PUMPS, VERTICAL TURBINE

DETAILS

CCN: [QXXW](#)

Document Type:

Parent CCN: [QWWQ](#)

RESOURCES

TAGS

Add Tag

Document [Company Information](#)



Centrifugal Fire Pumps, Vertical Turbine

[See General Information for Centrifugal Fire Pumps, Vertical Turbine](#)

FRONTIER SAFETY LIMITED
85 GREAT PORTLAND STREET
FIRST FLOOR
LONDON, W1W 7LT UNITED KINGDOM

EX28018

| Rated Capacity gpm | Model Dsg | Rated Net Pressure Range psi | Approx Speed rpm | Stages | | | | | | |
|--------------------|-----------------|------------------------------|------------------|-----------------|-----------------|-----------------|-----------------|---------|------|---|
| 1250 | 250FRNVT400-28 | 41-51 | 1480 | 1 | | | | | | |
| | | 82-102 | | 2 | | | | | | |
| | | 124-153 | | 3 | | | | | | |
| | | 165-305 | | 4-6 | | | | | | |
| 1500 | | 250FRNVT400-28 | 40-49 | 1480 | 1 | | | | | |
| | | | 77-97 | | 2 | | | | | |
| | | | 115-292 | | 3-6 | | | | | |
| 1500 | | | 250FRNVT400-28 | 58-71 | 1760 | 1 | | | | |
| | | | | 115-143 | | 2 | | | | |
| | | | | 173-214 | | 3 | | | | |
| | | | | 230-285 | | 4 | | | | |
| 2000 | | | | 250FRNVT400-28 | 63 | 1760 | 1 | | | |
| | | | | | 125 | | 2 | | | |
| | | | | | 188 | | 3 | | | |
| | | | | | 251 | | 4 | | | |
| 2000 | | | | | 250FRNVT550-26 | 40-44 | 1480 | 1 | | |
| | 77-88 | | | | | 2 | | | | |
| | 116-132 | | | | | 3 | | | | |
| | 155-176 | | | | | 4 | | | | |
| | 194-264 | | | | | 5-6 | | | | |
| 2000 | 250FRNVT550-26 | 57-66 | | | | 1760 | 1 | | | |
| | | 113-133 | | | | | 2 | | | |
| | | 170-199 | | | | | 3 | | | |
| | | 227-266 | 4 | | | | | | | |
| 2500 | | 250FRNVT550-26 | 61 | | | 1760 | 1 | | | |
| | | | 123 | | | | 2 | | | |
| | | | 184 | | | | 3 | | | |
| | | | 245 | 4 | | | | | | |
| 2500 | | | 300FRNVT860-43 | 50-82 | | 1480 | 1 | | | |
| | | | | 100-245 | | | 2-3 | | | |
| 3000 | | | | 300FRNVT860-43 | | 53-78 | 1760 | 1 | | |
| | | | | | | 105-235 | | 2-3 | | |
| 2500 | | | | | | 300FRNVT860-43 | 74-118 | 1760 | 1 | |
| | | | | | | | 149-236 | | 2 | |
| 3000 | | | | | | | 300FRNVT860-43 | 69-115 | 1760 | 1 |
| | | | | | 139-230 | | | 2 | | |
| 3500 | | | | | 300FRNVT860-43 | | | 73-111 | 1760 | 1 |
| | | | | | | | | 146-222 | | 2 |
| 4000 | | | 300FRNVT860-43 | | | | | 104 | 1760 | 1 |
| | | | | | | | | 207 | | 2 |
| 3500 | 350FRNVT1250-36 | | | 47-62 | | | | 1480 | 1 | |
| | | | | 93-124 | | | | | 2 | |
| | | | | 140-249 | | 3-4 | | | | |
| 4000 | | | | 350FRNVT1250-36 | | 45-61 | | 1480 | 1 | |
| | | 90-121 | | | | 2 | | | | |
| | | 135-243 | | | | 3-4 | | | | |
| 3500 | | 350FRNVT1250-36 | | | 56-74 | 1600 | 1 | | | |
| | | | | | 112-148 | | 2 | | | |
| | | | 168-295 | | 3-4 | | | | | |
| 4000 | | | 350FRNVT1250-36 | | 54-72 | 1600 | 1 | | | |
| | | | | | 107-144 | | 2 | | | |
| | | | | | 161-288 | | 3-4 | | | |
| 4000 | | | | | 350FRNVT1250-36 | 61-82 | 1700 | 1 | | |
| | | | | | | 122-163 | | 2 | | |
| | | | | | | 183-245 | | 3 | | |
| 4500 | | | | | | 350FRNVT1250-36 | 58-79 | 1700 | 1 | |
| | | | | | | | 116-159 | | 2 | |
| | | | | | | | 174-238 | | 3 | |
| 5000 | 350FRNVT1250-36 | | | | | | 229 | 1700 | 3 | |
| | | | | | | | 66-88 | | 1 | |
| 4000 | | | | | | | 350FRNVT1250-36 | 133-177 | 1760 | 2 |
| | | | | 199-265 | | | | 3 | | |
| | | | | 63-86 | | | | 1 | | |
| 4500 | | | | 350FRNVT1250-36 | | | | 126-172 | 1760 | 2 |
| | | 189-259 | | | | | | 3 | | |
| | | 249 | | | | | | 3 | | |
| 4000 | | 350FRNVT1250-36 | | | | | | 74-98 | 1840 | 1 |
| | | | 148-195 | | | | | 2 | | |
| | | | 222-293 | | | | | 3 | | |
| 4500 | | | 350FRNVT1250-36 | | | | | 70-95 | 1840 | 1 |
| | | | | | 141-190 | | | 2 | | |
| | | | | | 211-285 | | | 3 | | |

Last Updated on 2019-02-08

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

YOUR QUESTIONS, ANSWERED.

[My Tags](#) [Confirmation Letters & Other Features](#) [Contact Us](#)